7.5 HP Duplex


40.6 cfm @ 175 psi (Time Delay)
24 cfm @ 175 psi (Alternating)

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Platinum unit

Scan this QR code to learn more about this product



Model	Phase	Voltage	Tank	Length	Width	Height
DCI7521E120H-CI10	1	208-230	120 Gallon Horizontal	86	30	50
DCI7523E120H-CI10	3	208-230-460	120 Gallon Horizontal	86	30	50
Add -P to model number to make Platinum Unit						

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024