15 HP Duplex Enclosed Rotary Screw

70 dBA

110 cfm @ 150 psi

114 cfm @ 125 psi

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME powder coated air receiver
- Automatic tank drain
- Baldor electric motors
- Easy to read and access gauges
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Grasshopper style tank
- Heavy-duty air filter
- IEC contactors
- Omega profile rotors
- Single control solenoid operation
- SMART contact controls
- Sound dampening enclosure
- Spin on oil filter
- Spin on separator
- Stainless steel discharge lines
- Timed shutdown
- UL control components
- Vibration isolation pad
- 220 PSI maximum working pressure

CDR Compressor Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
DR153ENC-CDR	3	208-230/460-480	120 Gallon Horizontal	98	36	78	84	42

No Start Up Kit Required ■ Optional Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024