7.5 HP | 74 dBA Duplex Rotary Screw

52 cfm @ 150 psi
56 cfm @ 125 psi

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Automatic tank drain
- Baldor electric motors
- Easy to read and access gauges
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- IEC contactors
- Omega profile rotors
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- SMART contact controls
- Stainless steel discharge lines
- Timed shutdown
- UL control components
- Vibration isolation pads
- 220 PSI maximum working pressure



Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 230 Volt
DR73H120	3	208-230/460-480	120 Gallon Horizontal	80	48	60	36	18
DR71H120	1	208-230	120 Gallon Horizontal	80	48	60	64	N/A

No Start Up Kit Required ■ Optional Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024