50 HP Enclosed Rotary Screw

78 dBA

185 cfm @ 150 psi

215 cfm @ 125 psi

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation
- 220 PSI maximum working pressure



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R503ENC	3	208-230-460	N/A	Basic	57	44	60	125	63
R503ENC-CDR	3	208-230-460	120 Gallon Vertical	CDR	57	44	60	125	63

No Start Up Kit Required ■ Optional Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024