130 cfm Enclosed Hydraulic Driven Compressor

130 cfm @ 100 psi

125 cfm @ 150 psi

Features

- All hydraulic fluid and air connections on same side
- ASME/CRN certified safety valves
- Compressor load/unload operation
- Easy to remove compressor cover
- External NEMA 4 on/off switch
- Heavy-duty industrial rotary screw airend
- Hydraulic fluid flow regulator
- Hydraulic fluid pressure regulator
- Hydraulic fluid bypass valve
- IG SMART fluid control system
- Intake filter silencer
- NEMA 4 load/unload switch
- Steel mounting plate
- Vibration mounting pads
- 12 volt compressor air & oil cooler pack*
- 12 volt control system*

Options

- Cold weather heating package
- Cover color change
- High ambient temperature cooling package
- Hose reels
- Hydraulic fluid cooler
- Tank mounted
- 24 volt operation
- 110 volt operation

Scan this QR code to learn more about this product



Model	CFM@100psi	CFM@150psi	Hydraulic psi required	GPM Hydraulic Flow Required	Length	Width	Height
H-BM120R	130	125	2850	3	46	34	34

* Control voltage connection to be supplied by vehicle/equipment compressor is mounted to. Dimensions are representatives of package dimensions not total space required for mounting. Do not let hydraulic fluid exceed 190

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024