75 HP/325 cfm Open Rotary Screw

325 cfm @ 125 psi
285 cfm @ 150 psi

Basic Compressor Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin-on oil filter
- Spin-on separator
- TEFC drive motor (3 phase only)
- UL control components
- 220 PSI maximum working pressure

Platinum Compressor Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada

Platinum Stainless Features

- All Platinum features
- Stainless steel discharge lines
- Tank discharge ball valve
- Stainless steel 12 inch install line
- First oil and filter change



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS753H120	3	208-230-460	120 Horizontal	80	48	78	172	86
RS753BM-EVO	3	208-230-460	Base Mount	80	48	56	172	86
Add -P after part number to make Platinum Model								

No Start Up Kit Required ■ Optional Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024