5 HP Reciprocating

17.5 cfm @ 175 psi

Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

Scan this QR code to learn more about this product



Platinum Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
CI521E60V	1	208-230	60 Gallon Vertical	32	24	74	24	N/A
CI523E60V	3	208-230	60 Gallon Vertical	30	25	74	16	8
CI521E80V	1	208-230	80 Gallon Vertical	32	26	78	24	N/A
CI521E80H	1	208-230-460	80 Gallon Horizontal	63	24	45	16	N/A
CI523E80V	3	208-230	80 Gallon Vertical	32	26	78	24	8
CI523E80H	3	208-230-460	80 Gallon Horizontal	63	24	45	16	8
Add -P after model number to make Platinum Model								

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024